

DECLARATION OF PERFORMANCE According to Regulation (UE) 305/2011	
1.Unique identification code of the product type 2.Model and/or batch and/or serial number (art.11-4) 3.Intended uses of the product in accordance with the applicable harmonized technical specification, as foreseen by the manufactur 4.Name or registered trade mark and address of the manufacture (art. 11-5)	r : CS THERMOS SRL Via Padania,35 - 31020 San Vendemiano (TV) - Italia
5.Where applicable, name and address of the agent (art. 12-2) 6.Assessment and verification system for constancy of performant (annex 5)	: ce : System 3
7.Notified Laboratory	: KIWA CERMET ITALIA SpA (NB 0476)
Test report number (based on System 3)	3003081/C-430
8. Declared performance	
Harmonized technical specification	EN 14785:2006
Essential characteristics	Performance
Reaction to fire	A1
Distance to combustible materials	Minimum distance in mm :
	Rear = 500mm
	Side = 500mm
	Front = 1000mm
Diele of humaing final falling out	Floor =
Risk of burning fuel falling out Emission of combustion products (mg/Nm <sup>3</sup> -13% de O₂)	Pass
Nominal heat output	CO 123 NOx 96,4
Nominal fleat output	OGC 4,9
	PM 8,9
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	NPD
Mechanica resistance (to carry a chimney flue)	NPD
Thermal output	
Nominal heat output	9,26kW
Reduced nominal heat output	4,20kW
Efficiency	
Nominal heat output	91,78%
Reduced heat output	92,90%
Flue gas temperature	
Nominal heat output	103,7°C
Reduced heat output	75,5°C

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer in point 4.

San Vendemiano, 6-11-2018

Signed for and on behalf of the manufacturer:

Andrea Da Ros

Technical Manager

Reg. Imp. TV - C.F. / P.IVA 03892500269 Capitale Sociale € 100.000,00 i.v. Tel. +39 0438 62717 Fax +39 0438 453799