

DECLARATION OF PERFORMANCE According to Regulation (UE) 305/2011	
 Unique identification code of the product type Model and/or batch and/or serial number (art.11-4) Intended uses of the product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer (art. 11-5) 	
5.Where applicable, name and address of the agent (art. 12-2) 6.Assessment and verification system for constancy of performanc (annex 5)	: e : System 3
7.Notified Laboratory	: KIWA CERMET ITALIA SpA (NB 0476)
,	2004051/01
Test report number (based on System 3)	
8. Declared performance	
Harmonized technical specification	EN 14785:2006
Essential characteristics	Performance
Reaction to fire	A1
Distance to combustible materials	Minimum distance in mm :
	Rear = 500mm
	Side = 500mm
	Front = 1000mm
	Floor =
Risk of burning fuel falling out	Pass
Emission of combustion products (mg/Nm ³ -13% de O ₂)	CO 84
Nominal heat output	NOx 103
	OGC 2
	PM 12
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	NPD
Mechanica resistance (to carry a chimney flue)	NPD
Thermal output	
Nominal heat output	11,5kW
Reduced nominal heat output	5,0kW
Efficiency	
Nominal heat output	92,30%
Reduced heat output	93,30%
Flue gas temperature	
Nominal heat output	133,4°C
Reduced heat output	94.5°C

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer in point 4.

San Vendemiano, 07-10-2021

Signed for and on behalf of the manufacturer:

Andrea Canzian

Technical Manager

Reg. Imp. TV - C.F. / P.IVA 03892500269 Capitale Sociale € 100.000,00 i.v. Tel. +39 0438 62717 Fax +39 0438 453799