

Characteristics when operating with the preferred fuel only							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output				Useful efficiency (NCV as received)			
Nominal heat output	P _{nom}	9,2	kW	Useful efficiency at nominal heat output	$\eta_{th,nom}$	91,7	%
Minimum heat output (indicative)	P _{min}	4,2	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{th,min}$	92,9	%


Auxiliary electricity consumption				Type of heat output/room temperature control (select one)	
At nominal heat output	el _{max}	0,110	kW	Single stage heat output, no room temperature control	NO
At minimum heat output	el _{min}	0,062	kW	Two or more manual stages, no room temperature control	NO
In standby mode	el _{sb}	0,004	kW	With mechanic thermostat room temperature control	NO
Permanent pilot flame power requirement				With electronic room temperature control	NO
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW	With electronic room temperature control plus day timer	NO
				With electronic room temperature control plus week timer	YES
				Other control options (multiple selections possible)	
				Room temperature control, with presence detection	NO
				Room temperature control, with open window detection	NO
				With distance control option	NO

Contact details	Name and address of the manufacturer or its authorised representative
(*) PM = particulate matter, OGCs = organic gaseous compounds, CO = carbon monoxide, NO _x = nitrogen oxides. (**) Only required if correction factors F(2) or F(3) are applied.	

www.csthermos.it
info@csthermos.it
Tel. +39 0438 62717

CS THERMOS SRL
Via Padania, 35
31020 SAN VENDEMIANO (TV)
ITALIA

Signed for and on behalf of the manufacturer by
Andrea Canzian, Technical Manager



San Vendemiano, 01.12.2021